



Specifications Noxion LED Downlight Apollo V2.0 15W  
1860lm 60D - 830/840 CCT | 175mm - Cutout 150mm  
- Dali Dimmable

[View Product](#)

## General Information

|                          |                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|
| SKU                      | 251735                                                                              |
| EAN                      | 8719157054928                                                                       |
| manufacturer_code        | 8719157054928                                                                       |
| Brand                    | Noxion                                                                              |
| Manufacturer Name        | Noxion LED Downlight Apollo V2.0 15W 1860lm 2CCT Cutout Ø150mm<br>Frame Ø175mm DALI |
| Any Lamp all-in warranty | 6 Years                                                                             |
| Average Lifetime (h)     | 100000                                                                              |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Tiltable                    | No                               |
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 30                               |
| Wattage                     | 15W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Dimmable with Dali               |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light Colour Options        | CCT                              |

|                       |                                |
|-----------------------|--------------------------------|
| Beam Angle (degree)   | 60                             |
| Luminous Flux (Lumen) | 1860lm                         |
| Lumen per watt        | 128                            |
| Power factor          | >0.90                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Finish of Reflector   | White                          |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 150                           |
| IP-Rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Series                 | Apollo                        |

## Dimensions

Height (mm)

**Why Any-lamp?**

108

Diameter (mm)

175



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

Type of sensor

No Sensor

